Kaiko

MIGRATION GUIDE

Options Tickers

HTTP REST

Amberdata → Kaiko

2026

www.kaiko.com

1 At a glance

What this endpoint gives you. Historical ticker snapshots for one option contract: best bid and ask with sizes, last trade, mark and index price, implied volatilities, Greeks, open interest and 24-hour statistics.

What changes for you

- **One Kaiko path for every market.** The instrument moves from the path to a query parameter and the market is set with `class` (see §2–3).
- **Field names move to snake_case**, e.g. `bidVolume` → `bid_volume` (see §5).
- **Timestamps are ISO 8601 strings.** The nanosecond and per-side timestamp fields are dropped; a `timestamp` field is added.
- **One exchange per call.** Amberdata accepts a comma-separated list of exchanges for options (default: all); **Kaiko takes exactly one exchange**. Call once per exchange.
- **24-hour statistics are named explicitly**: `low` / `high` become `low_24h` / `high_24h`, and `open_24h` is added. Five Amberdata fields have no Kaiko equivalent (see §5).
- **Numeric values are returned as strings**, not JSON numbers. Parse them as decimals.
- Each row now carries its `class`. The response envelope is simpler, with pagination in `meta.next_url` (see §4).

Coverage & distribution

Data type: Option ticker snapshots with IVs, Greeks, open interest and 24-hour statistics

Markets: CEX options

Request scope: One instrument per call; Amberdata range limited to 1 hour per call; Kaiko has no range cap: any range is served page by page (`page_size`)

Distribution: REST API

2 Endpoint & authentication

	Amberdata (today)	Kaiko (new)
Method	GET	GET
Base URL	`https://api.amberdata.com/markets`	`https://api.kaiko.io`
Path	`/options/tickers/{instrument}`	`/market-data/tickers`
Auth	API key header `x-api-key`	API key header `X-Api-Key` (same mechanism, new key)

On Kaiko the instrument moves from the path to a query parameter, and the market is selected with `class`. The same Kaiko path serves spot, futures and options tickers.

Kaiko API family: New API grammar

This endpoint uses Kaiko's new `market-data` grammar: every parameter is a query parameter and responses share the `data` + `meta` envelope. Kaiko's Classic (versioned) endpoints, such as Trades, use a different URL structure and envelope.

3 Request parameters

All Kaiko parameters are query parameters.

Amberdata param	Kaiko param	Change	Notes
`instrument` (path, required)	`instrument`	RENAMED	One instrument per call on both sides. Kaiko instrument code, e.g. `btc13nov2668000cusdt` (Bybit) (see §6).
—	`class`	NEW	Market: `option`.
`exchange` (query, required)	`exchange`	RENAMED	Amberdata: comma-separated list, all exchanges by default. Kaiko exchange code, e.g. `bbit`, `okex` (see §6). **One exchange per call on Kaiko** (required).
`startDate` (optional)	`start_time`	RENAMED	**Inclusive on both sides.** Amberdata accepts seconds, milliseconds or ISO 8601 and defaults to the beginning of the current hour. Kaiko takes ISO 8601 (e.g. `2026-10-26T12:34:30.000Z`). **Optional: without dates, Kaiko returns the last hour.** With dates, there is no range cap: the range is served page by page (`page_size`).
`endDate` (optional)	`end_time`	RENAMED	**Exclusive on both sides.** ISO 8601 on Kaiko. Optional; defaults to now.
`sortDirection` (optional)	`sort`	RENAMED	Amberdata: `asc` (default) or `desc`, only for ranges within the last 24 hours. Kaiko: `asc` or `desc` (default, newest first).
`timeFormat` (optional)	—	REMOVED	Amberdata can return milliseconds, ISO 8601 or human-readable timestamps (default `hr` on spot and futures). Kaiko always returns ISO 8601 strings.
—	`page_size`	NEW	Optional. Number of rows per page.
`api-version` (header, optional)	`api_version`	RENAMED	A header on Amberdata; a query parameter on Kaiko, e.g. `2026-10-01`.
`Accept-Encoding` (header, required)	`Accept-Encoding`	IDENTICAL	Required by Amberdata (`gzip, deflate, br`); supported by Kaiko.

Error codes

Common to Kaiko's New API grammar endpoints:

- `400` : invalid parameter (value, format or precision not accepted).
- `403 not_entitled` : the requested asset or instrument is outside your licence. Lists are authorised all or nothing.
- `403 history_out_of_entitlement` : the time window goes beyond your key's history entitlement, including the default window when no dates are sent.
- `404 unknown_instrument` : a code that is not an instrument of the requested `class` / exchange; the response names it.

4 Response envelope & metadata

The fields around the data, the wrapper your parser reads before reaching the numbers. This envelope is **identical on every Amberdata endpoint**.

Amberdata field	Kaiko field	Change	Notes
`status`	—	REMOVED	HTTP-style status integer (200). Not in the Kaiko body; rely on the HTTP status code.
`title`	—	REMOVED	"OK" label, no direct Kaiko equivalent.
`description`	—	REMOVED	Free-text status description.
`payload.data`	`data`	RENAMED	**Array** holding the ticker rows (see §5), now at the top level.
`payload.metadata`	`meta`	RENAMED	Metadata object, after `data`.
`payload.metadata.api-version`	`meta.api_version`	RENAMED	Date version of the API used, e.g. `2023-09-30` on Amberdata, `2026-10-01` on Kaiko.
—	`meta.count`	NEW	Number of items returned in `data` on this page.
`payload.metadata.next`	`meta.next_url`	RENAMED	Full URL of the next page when results are paginated (a cursor URL on Amberdata). Call it as-is until it is no longer returned.
—	`meta.url`	NEW	The query as requested, with every parameter it carries.

5 Response - data fields

One row per ticker update. All Kaiko numeric values are returned as decimal strings; parse them as decimals.

Amberdata field	Kaiko field	Change	Notes
`instrument`	`instrument`	RENAMED	Same name, Kaiko instrument code (see §6).

Amberdata field	Kaiko field	Change	Notes
`exchange`	`exchange`	RENAMED	Same name, Kaiko exchange code, e.g. `bbit`, `okex` (see §6).
—	`class`	NEW	Market of the row (e.g. `spot`, `option`).
`exchangeTimestamp`	`exchange_timestamp`	RENAMED	Timestamp provided by the exchange. Amberdata falls back to its own collection time when the exchange provides none; Kaiko keeps the two apart (`exchange_timestamp` and `timestamp`). Format: milliseconds or a human-readable string on Amberdata depending on `timeFormat`; ISO 8601 string on Kaiko (e.g. `2026-10-28T14:26:26.451Z`).
`exchangeTimestampNanoseconds`	—	REMOVED	Sub-millisecond part of the Amberdata timestamp. Kaiko timestamps carry millisecond precision.
—	`timestamp`	NEW	**Kaiko collection timestamp** (when Kaiko received the update), ISO 8601.
`bid`, `ask`, `mid`	`bid`, `ask`, `mid`	RENAMED	Same names; number → decimal string.
`last`	`last`	RENAMED	Same name; decimal string. Can be `null` on both sides when the venue does not publish it.
`bidVolume`	`bid_volume`	RENAMED	Size at the best bid; decimal string.
`askVolume`	`ask_volume`	RENAMED	Size at the best ask; decimal string.
`lastVolume`	`last_volume`	RENAMED	Size of the last trade.
`baseVolume`, `quoteVolume`	`base_volume`, `quote_volume`	RENAMED	Traded volume in base and quote asset over a **rolling 24 hours**.
`volume`	`base_volume`	RENAMED	Traded volume over a rolling 24 hours, in base asset. Amberdata `volume` and `baseVolume` both map to Kaiko `base_volume`.
`volumeUSD`	—	REMOVED	No Kaiko equivalent.
`sequence`	`sequence`	IDENTICAL	Venue sequence number as a string; `null` when the venue provides none.
`markPrice`	`mark_price`	RENAMED	Exchange mark price.
`indexPrice`	`index_price`	RENAMED	Exchange index price.
`underlyingPrice`	`underlying_price`	RENAMED	Price of the underlying.
`underlyingIndex`	—	REMOVED	No Kaiko equivalent.

Amberdata field	Kaiko field	Change	Notes
`settlementPrice`	`settlement_price`	RENAMED	`null` in both samples.
`estimatedDeliveryPrice`	—	REMOVED	No Kaiko equivalent.
`low` , `high`	`low_24h` , `high_24h`	RENAMED	Kaiko names the window: rolling 24 hours. Amberdata does not document its window.
—	`open_24h`	NEW	Opening price of the rolling 24-hour window.
`priceChange`	—	REMOVED	No direct field on Kaiko.
`openInterest`	`open_interest`	RENAMED	Open interest.
`minPrice` , `maxPrice`	`min_price` , `max_price`	RENAMED	Venue price limits; `null` in both samples.
`markIv` , `bidIv` , `askIv`	`mark_iv` , `bid_iv` , `ask_iv`	RENAMED	Implied volatility as a decimal fraction on both sides (0.4716 = 47.16%).
`delta` , `gamma` , `theta` , `vega` , `rho`	same names	RENAMED	Same names; decimal strings.
`interestRate`	—	REMOVED	No Kaiko equivalent.
`state`	`state`	IDENTICAL	`null` in both samples.
`askTimestamp` , `bidTimestamp`	—	REMOVED	Per-side timestamps, `null` on Amberdata.
`askTimestampNanoseconds` , `bidTimestampNanoseconds`	—	REMOVED	Sub-millisecond parts of the per-side timestamps.

6 Exchange & instrument names

Kaiko identifies venues and instruments with its own normalized codes, which differ from Amberdata's names. Codes can also differ by market for the same venue (e.g. Binance spot and options).

Reference

The mapping rules and the full code lists apply to every endpoint and are described in the **Exchange, Asset & Instrument Mapping** migration guide (`exchange-instrument-asset-codes.pdf`).

7 Will your values change?

Short answer

Prices, IVs and Greeks are published by the exchange, so values should match once rows are aligned on time.

- **Update capture.** A ticker row is a snapshot of the top of the book. Row frequency and capture timing can differ between providers, so rows will not match one-to-one; align them on time before comparing. Kaiko records each ticker update in real time, as received from the exchange: row frequency follows the venue (e.g. about 1 second on Deribit spot, 100 ms on Bybit perpetuals).
- **Premium units follow the venue.** Some venues quote options in the underlying coin: in the Kaiko OKX sample, the ETH call is quoted at `0.0925` (ETH). Compare like with like.
- **Timestamp precision.** Amberdata adds nanoseconds in a separate field; Kaiko timestamps carry milliseconds.
- **Number representation.** Kaiko returns decimal strings, which keep the exact digits; Amberdata returns JSON numbers. Compare as decimals, not as text.

8 Before / after example

Request

Amberdata

```
GET https://api.amberdata.com/markets
    /options/tickers
    /BTC-13NOV26-68000-C-USDT
    ?exchange=bybit
x-api-key: <your key>
```

Kaiko

```
GET https://api.kaiko.io
    /market-data/tickers
    ?exchange=bbit
    &class=option
    &instrument=btc13nov2668000cusdt
X-Api-Key: <your key>
```

Response

Real samples. The two calls cover different venues and contracts, so values are not comparable.

Amberdata


```
{
  "status": 200,
  "title": "OK",
  "description": "Successful request",
  "payload": {
    "metadata": {
      "next": "https://api.amberdata.com/...?
cursor=...",
      "api-version": "2023-09-30"
    },
    "data": [
      {
        "instrument": "BTC-13NOV26-68000-C-USDT",
        "exchange": "bybit",
        "exchangeTimestamp": 1793110986088,
        "exchangeTimestampNanoseconds": 0,
        "bid": 12315,
        "mid": 12417.5,
        "ask": 12520,
        "last": 0,
        "bidVolume": 2,
        "askVolume": 2,
        "lastVolume": null,
        "baseVolume": null,
        "quoteVolume": null,
        "sequence": null,
        "underlyingPrice": 80223.8,
        "underlyingIndex": null,
        "settlementPrice": null,
        "markPrice": 12382.63435471,
        "low": 0,
        "high": 0,
        "volume": 0,
        "volumeUSD": null,
        "priceChange": 0,
        "openInterest": 0,
        "minPrice": null,
        "maxPrice": null,
        "markIv": 0.4716,
        "interestRate": null,
        "indexPrice": 80019.29297686,
        "rho": null,
        "vega": 16.49502603,
        "delta": 0.9542666,
        "gamma": 0.00001186,
        "theta": -23.24226861,
        "bidIv": 0.4243,
        "askIv": 0.5414,
        "estimatedDeliveryPrice": null,
        "state": null,
        "askTimestamp": null,
        "bidTimestamp": null,
        "askTimestampNanoseconds": null,
        "bidTimestampNanoseconds": null
      },
      ...
    ]
  }
}
```


Kaiko


```
{
  "data": [
    {
      "ask": "0.0925",
      "ask_iv": "0.5163663891",
      "ask_volume": "7.300000000000001",
      "base_volume": "23.8",
      "bid": "0.092",
      "bid_iv": "0.5130094622",
      "bid_volume": "172.70000000000002",
      "class": "option",
      "delta": "0.486488336",
      "exchange": "okex",
      "exchange_timestamp":
"2026-10-26T12:34:30.08Z",
      "gamma": "0.906302846",
      "high_24h": "0.138",
      "index_price": "2331.48",
      "instrument": "ethusd2612252300c",
      "last": "0.091",
      "last_volume": "1",
      "low_24h": "0.0905",
      "mark_iv": "0.5141935077",
      "mark_price": "0.0921849510699197",
      "max_price": null,
      "mid": "0.09225",
      "min_price": null,
      "open_24h": "0.0905",
      "open_interest": "266",
      "quote_volume": null,
      "rho": null,
      "sequence": null,
      "settlement_price": null,
      "state": null,
      "theta": "-0.0006806466",
      "timestamp": "2026-10-26T12:34:30.08Z",
      "underlying_price": "2345.6898954447",
      "vega": "0.0015834142"
    },
    ...
  ],
  "meta": {
    "api_version": "2026-10-01",
    "count": 2,
    "next_url": "https://api.kaiko.io/market-data/
tickers?...",
    "url": "https://api.kaiko.io/market-data/
tickers?..."
  }
}
```